

Platu Class Rule Amendments – Platu Thailand OMJ Series

Section B – Boat Eligibility

All Boats are Built to Class Specifications, have Class approved Masts & all hardware / deck fittings comply as per OD Rules. Certificate, Buttons & ID Stickers Not Required.

Sections B1 & B2 inclusive are Not Required

PART II – REQUIREMENTS AND LIMITATIONS

Section C – Conditions for Racing

C.4.1 Advertising – Amend WS Regulation 20.4.1.5 to Advertising Permitted to 50% of each Sail, however, Must Not impede Class Insignia, National Letters or Sail Numbers.

C.5.1 Portable Equipment

C5.1 (a) (6) Emergency flares optional not mandatory

C.6 BOAT WEIGHT

C.6.1 (j) Spinnaker Tweakers

C.6.1 (k) Mainsheet Blocks

C6.1 (q) Remove Battery

C.6.1.(t) “All Bunk Hatch Covers”

Toilet - If Installed, can be removed OR assessed weight of 10Kg & Not included in Total weight of Boat

C6.2 (a) corrector weights may be added by cement

C 7.2 .1 (b) Amended to “Bunk Hatch Covers”

C7.3(b) 4 - Bilge pump fitting may be faired in

C.10 SAILS

C.10.1 (b) - Not Required

C.10.2 (a) Not more than 1 Mainsail, minimum 2 Jibs (not more than 3 Jibs) & Not More than 2 Spinnakers shall be carried on board whilst Racing

C.10.2 (b) & (c) - Delete, Not Required

C.10.3 Mainsail ID (a) Insignia, National Letter & Number Preferred

(b) Not Required

C.10.4 Spinnaker ID (a) Not Required

Section D Hull

D2.4 (a) WS Plaque Not Required

D2.4 (b) Builders Number will be displayed on the Transom

D.5.1 Fittings

D5.1 (a)

- Wire may be replaced with rope substitute (e.g. Dyneema) with equivalent minimum Breaking Strain of 3mm Wire
- A bilge pump may be replaced by a sturdy , 10 litre minimum, bucket, and sponge .

D.5.1 (b) - Jib Cuningham System allowed with 1:1 Jib Halyard ONLY

Section F Rig

F.2.3 - Not Required

F.3.4 DIMENSIONS

Spinnaker Pole eye fitting may be fitted between 2,150 mm to 2,500 mm above the Mast Datum Point.

F6 Standing Rigging

F.6.1 Materials Dyform Wire is allowed

F.6.3 Forestay Fittings

F.6.3 (a) (1) Amended to allow a turnbuckle or plate/holes/pins on the forestay.

F.6.4 Backstay – Dyneema rope 3 – 4mm diameter allowed

Section G Sails

G.2.1

(a) Shall conform to Class Dimensions and Measurements listed in this section.

(b) as above

G.2.2 (a) and (b) Certification is Not Required

G3 Mainsail

G.3.2 Materials – Carbon Fibre is Not Permitted

G4 Headsails

G.4.1 Materials – Carbon Fibre is Not Permitted